



\*



# 1.0mm Pitch 2.0H Flip-Lock ZIF

# FPC 1.0 Series

# **FEATURES & BENEFITS:**

The product is widely used in AV, Digital devices, Cameras, Automobile AV, TV, Calculators, Cash registers, Telephones, MP3,mp4,CD-ROM,VCD.DVD, Copiers, Printers, Scanners, Notebook computers, Wireless instrumentation, Disc devices and Space ships and etc.

## SPECIFICATION:

#### + Electrical:

- Voltage: 50V AC Max.
- Current Rating: 0.4A DC Max.
- Contact Resistance:20 mΩ Max.
- Insulation Resistance:  $500M\Omega$  Min.
- Dielectric Strength:200V AC (rms) for 1 minute

#### Mechanical:

- Contact Retention Force: 0.08 kgf Min.
- FPC/FFC Retention Force: 0.04 kgf Min.

## REFERENCE INFORMATION:


- The kind of connector has its pitch 1.0, and can be divided into 4~50 screens type. Moreover, it features high density, small volume and easy use.
- Package: Pipe package or roll package
- Designed in: mm/inch

## Physical:

- Housing: LCP UL94V-0 white
- Actuator: LCP UL94V-0 black
- Contact: Phosphor Bronze Gold or Tin plated on Ni over All
- LEG: Phosphor Bronze Matte Tin plated on Nickel over all
- Operating Temperature: -25° ~+85° €

# **ORDERING INFORMATION AND DIMENSIONS:**

# Part NO.:



Number of	Dimension			
Contacts	Α	В	С	D
04	8.90	3.00	8.50	5.10
05	9.90	4.00	9.50	6.10
06	10.90	5.00	10.50	7.10
07	11.90	6.00	11.50	8,10
08	12.90	7,00	12,50	9,10
09	13.90	8.00	13.50	10.10
10	14.90	9,00	14,50	11,10
11	15.90	10.00	15,50	12.10
12	16.90	11,00	16.50	13,10
13	17.90	12,00	17,50	14.10
14	18.90	13,00	18.50	15,10
15	19.90	14,00	19,50	
16	20.90	15.00	20.50	
17	21,90	16,00	21.50	18,10
18	22.90	17.00	22.50	19.10
19	23.90	18.00	23.50	20.10
20	24.90	19,00	24.50	
21	25.90	20.00	25.50	22.10
22	26,90	21.00	26.50	
23	27.90	22.00	27.50	
24	28.90	23.00	28.50	25.10
25	29.90	24.00	29.50	26,10
26	30,90	25,00	30.50	27,10
27	31,90	26.00	31.50	28,10
28	32,90	27,00	32,50	29,10
29	33.90	28.00	33.50	30.10
30	34.90	29,00	34.50	31,10
31	35.90	30,00	35.50	32.10
32	36.90	31,00	36.50	33,10